

DRYING TIME :

Normally dries in 1-3 hours and can be walked on after drying overnight. 48 hours are generally required before heavy foot traffic. Low temperatures and high humidity can extend drying and curing time.

MAINTENANCE:

Small scratches may be repaired with a small amount of Xylene and a brush. Apply a small amount of Xylene to the affected area and re-flow the sealer into the scratch. For larger areas or for re-coating, make sure the surface is clean, completely dry and free from contaminants. Re-apply a thin, light coat to the wear areas. Lap lines may be feathered with xylene .

LIMITATIONS:

DO NOT APPLY when air or surface temperatures are below 50 degrees Fahrenheit (10 C) or are expected to fall there before the coating can dry.

DO NOT APPLY to a wet or damp surface

DO NOT APPLY when it may rain or if dew may condense on the surface before PAVER SEALER 335 will have a chance to dry.

NOT FOR USE on STAMPED CONCRETE!

NOT FOR USE on FIRED BRICK, CERAMIC, OR WIRE CUT TILE!

DO NOT OVER APPLY! Blushing , crazing, dirt pick-up and tire printing may result.

TECHNICAL DATA:

SOLIDS/WEIGHT	33.5 %
COVERAGE	125-250 SQ.FT./GAL DEPENDING ON POROSITY AND TEXTURE OF SUBSTRATE.
CLEAN-UP	XYLENE/TOLUENE
VOC CONTENT	LESS THAN 600 G/L. / 5.0 LB./GAL.
APPEARANCE	CLEAR
LIGHT STABILITY	EXCELLENT
DURABILITY	EXCELLENT
TENSILE STRENGTH	EXCELLENT
BONDING	GOOD
EPA AIM CATEGORY	WATER REPELLENT SEALER
WATER RESISTANCE	EXCELLENT
GASOLINE RESISTANCE	FAIR
CHLORINE RESISTANCE	GOOD
ANTI-FREEZE	GOOD
SOFT DRINKS, CITRUS	GOOD
TANNING/BODY OILS	GOOD
C.O.F.	.62-.84 *

* COEFFICIENT OF FRICTION WILL VARY DEPENDING UPON APPLICATION METHOD, FILM BUILD, SUBSTRATE PROFILE, AND SURFACE CONTAMINATION. REFERENCE LISTED IS FOR A SMOOTH TROWELLED SURFACE.

MANUFACTURED BY: TUF-TOP COATINGS DIVISION OF MARINE INDUSTRIAL PAINT CO.,INC. ST. PETERSBURG, FL.
PHONE 727-527-3382 800-459-3382 FAX 727-521-1405 WWW.TUF-TOP.COM

LIMITATION OF LIABILITY: The Manufacturer and/or seller warrants that if any goods supplied prove defective in workmanship or material, that Manufacturer and/or seller shall replace them or refund the purchase price. This warranty is made in lieu of any and all other warranties expressed or implied. Before application, the User shall determine the suitability of the product for his intended and User assumes all risks and liabilities. whatsoever in connection therewith Under no circumstances shall the Manufacturer and/or Seller be liable for incidental, consequential or other damages for alleged negligence, breach or warranty, or strict liability arising out of use or handling of this product. The sole liability of Manufacturer and/or Seller for any claims arising out of the use or sale of the product shall be for User's purchase price.