

## DRYING TIME:

Normally dries in 24 hours and can be walked upon after drying overnight 75 degrees Fahrenheit. 72 hours are generally required before driving vehicles on. Maximum cure will be achieved in 5-7 days. Low temperatures and high humidity can extend drying and curing time. Moisture and dew on the surface will halt the curing until it dries off again and should be taken into consideration.

---

## CLEAN UP:

Clean equipment with warm soapy water. Clean all equipment immediately after use. Once SAFE QUARTZ-E dries, strong solvents must be used to clean equipment.

---

## COVERAGE:

Smooth Concrete - 50 - 80 sq.ft./gal per coat

NOTE: ACTUAL COVERAGE RATES VARY DEPENDING ON SURFACE TEXTURE AND METHOD OF APPLICATION.

---

## LIMITATIONS:

DO NOT APPLY when air or surface temperatures are below 50 degrees Fahrenheit or are expected to fall there before the coating can dry.

DO NOT APPLY when air or surface temperatures exceed 90 degrees Fahrenheit or lap marking may occur.

DO NOT APPLY to wet or damp surfaces.

DO NOT APPLY when it may rain or if dew may condense on the surface before paint will have a chance to dry.

ALLOW FOR SLOW DRYING during high humidity.

DO NOT ALLOW TO FREEZE. Store above 32 degrees Fahrenheit. ( 0 C )

RESISTANT TO gasoline, oil, grease, and most chemicals. Brake fluid must be wiped from the surface as soon as possible as it may soften the film temporarily.

NOT RECOMMENDED FOR EXTERIOR USE., OR IN AREAS THAT RECEIVE FULL SUN. CHALKING MAY RESULT.

---

## TECHNICAL DATA:

SOLIDS/VOLUME	60 %
SOLIDS/WEIGHT	78 %
COVERAGE	35-75 SQUARE FEET PER GALLON PER COAT DEPENDING ON THE POROSITY AND TEXTURE OF THE SUBSTRATE
DILUENT	WATER
CLEAN-UP	SOAP AND WATER
VOC CONTENT	80 GR/LITER
ODOR	SLIGHT
APPEARANCE	DEPENDS ON COLOR
LIGHT STABILITY	FAIR
DURABILITY	EXCELLENT
ABRASION RESISTANCE	VERY GOOD-EXCELLENT
GASOLINE RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	VERY GOOD
WATER RESISTANCE	EXCELLENT
BONDING	EXCELLENT
POT LIFE	1.5-2.5 HRS @ 70F.

---

**MANUFACTURED BY: TUF-TOP COATINGS DIVISION OF MARINE INDUSTRIAL PAINT CO., INC. ST. PETERSBURG, FL.  
PHONE 727-527-3382 800-459-3382 FAX 727-521-1405 WWW.TUF-TOP.COM**

**LIMITATION OF LIABILITY:** The Manufacturer and/or seller warrants that if any goods supplied prove defective in workmanship or material, that Manufacturer and/or seller shall replace them or refund the purchase price. This warranty is made in lieu of any and all other warranties expressed or implied. Before application, the User shall determine the suitability of the product for his intended and User assumes all risks and liabilities, whatsoever in connection therewith. Under no circumstances shall the Manufacturer and/or Seller be liable for incidental, consequential or other damages for alleged negligence, breach or warranty, or strict liability arising out of use or handling of this product. The sole liability of Manufacturer and/or Seller for any claims arising out of the use or sale of the product shall be for User's purchase price.